

Urządzenie 2K (dwukomponentowe)

GRACO ProMix 2KS elektroniczny system dozowania materiałów dwuskładnikowych

Marka: GRACO



Opis produktu

Urządzenie dwuskładnikowe GRACO ProMix 2KS

Urządzenie GRACO ProMix 2KS to elektroniczny system dozowania materiałów dwuskładnikowych.

Więcej szczegółów w zakładce do pobrania.

| ProMix 2KS Manual System | |
|---|---|
| Maximum working air pressure | 7.0 bar, 0.7 MPa |
| Air supply | 5.2–7.0 bar, 0.5–0.7 MPa |
| Air filter inlet size | 3/8 npt(f) |
| Air filtration for air logic and purge air (Graco-supplied) | 5 micron (minimum) filtration required; clean and dry air |
| Air filtration for atomizing air (user-supplied) | 30 micron (minimum) filtration required; clean and dry air |
| Mixing ratio range | 0.1:1–50:1 |
| Fluids handled | one or two component: solvent and waterborne paints, polyurethanes, epoxies, acid catalyzed varnishes, moisture sensitive isocyanates |
| Viscosity range of fluid | 20–5000 cps |
| Fluid filtration (user-supplied) | 100 mesh minimum |
| External power supply requirements | 85–250 Vac, 50/60 Hz, 2 amps maximum draw, 15 amp maximum circuit breaker required, 8 to 14 AWG power supply wire gauge |
| Operating temperature range | 5–50°C |
| Environmental conditions rating | indoor use, pollution degree (2), installation category II |
| Wetted parts | 303 and 304 stainless steel, Tungsten carbide (with nickel binder), perfluoroelastomer, PTFE |
| Maximum fluid working pressure | |
| Base system | 280 bar, 28 MPa |
| Low pressure color change | 21 bar, 2.1 MPa |
| High pressure color change | 210 bar, 21 MPa |
| Coriolis Meter | 161 bar, 16.1 MPa |
| Fluid Flow Rate Range | |
| G3000, G250 Meter | 75–3800 cc/min |
| G3000HR, G250HR Meter | 38–1900 cc/min |
| Coriolis Meter | 20–3800 cc/min |
| S3000 Solvent Meter (accessory) | 38–1900 cc/min |
| Fluid Porting | |
| Flow Meter Fluid Inlet | 1/4 npt(f) |
| Dose Valve/Color Valve Adapter Inlets | 1/4 npt(f) |
| Fluid Outlet Size (static mixer) | 1/4 npt(f) |
| Noise Level | |
| Sound pressure level | below 70 dBA |
| Sound power level | below 85 dBA |

| ProMix 2KS Automatic System | |
|---|---|
| Maximum working air pressure | 7.0 bar, 0.7 MPa |
| Air supply | 5.2–7.0 bar, 0.5–0.7 MPa |
| Air filter inlet size | 3/8 npt(f) |
| Air filtration for air logic and purge air (Graco-supplied) | 5 micron (minimum) filtration required; clean and dry air |
| Air filtration for atomizing air (user-supplied) | 30 micron (minimum) filtration required; clean and dry air |
| Mixing ratio range | 0.1:1–50:1 |
| On-ratio accuracy | up to +/- 1%, user selectable |
| Fluids handled | one or two component: solvent and waterborne paints, polyurethanes, epoxies, acid catalyzed varnishes, moisture sensitive isocyanates |
| Viscosity range of fluid | 20–5000 cps |
| Fluid filtration (user-supplied) | 100 mesh minimum |
| External power supply requirements | 85–250 Vac, 50/60 Hz, 2 amps maximum draw, 15 amp maximum circuit breaker required, 8 to 14 AWG power supply wire gauge |
| Operating temperature range | 5–50°C |
| Environmental conditions rating | indoor use, pollution degree (2), installation category II |
| Wetted parts | 303 and 304 stainless steel, Tungsten carbide (with nickel binder), perfluoroelastomer, PTFE |
| Maximum fluid working pressure | |
| Base system | 275.8 bar, 27.58 MPa |
| Low pressure color change | 20.6 bar, 2.07 MPa |
| Coriolis Meter | 158.6 bar, 15.86 MPa |
| RoboMix system | 13.1 bar, 1.31 MPa |
| Flow control | 13.1 bar, 1.31 MPa |
| Fluid Flow Rate Range | |
| G3000, G250 Meter | 75–3800 cc/min |
| G3000HR, G250HR Meter | 38–1900 cc/min |
| Coriolis Meter | 20–3800 cc/min |
| S3000 Solvent Meter (accessory) | 38–1900 cc/min |
| Fluid Porting | |
| Flow Meter Fluid Inlet | 1/4 npt(f) |
| Dose Valve/Color Valve Adapter Inlets | 1/4 npt(f) |
| Fluid Outlet Size (static mixer) | 1/4 npt(f) |
| Noise Level | |
| Sound pressure level | below 70 dBA |
| Sound power level | below 85 dBA |

Parametry techniczne

| | |
|--------------------------|---|
| Marka | GRACO |
| Producent odpowiedzialny | GRACO DISTRIBUTION BV Belgia 3630 Maasmechelen Slakweidestraat 31 tr |

Galeria



Znajdź produkt na:

<https://techmal.pl/graco-promix-2ks-elektroniczny-system-dozowania-materialow-dwuskładnikowych>